

PD8045 Cut Resistant Work Gloves (Cut 3)

Liner: HDPE Cut Level 3 LinerCoating: PU Palm Coating

Cuff : Knit Wrist Cuff

• Color Available: Black, Grey, White, Green, Yellow etc

• Size: 7' -11' (S,M,L,XL,XXL)

• Package: 120 Pairs/CTN (72X27X26CM)

• CE EN420:2003+A1:2009

CE EN388:2016

 Application: Construction, Road & Building Workers, Glasses Installation, Logistics, Mechanics, Factory Workshop, Garden & other Cut-Resistant Workplaces etc



Mechanical Hazard EN388:2016	
Protection Offered	Performance Levels
Abrasion Resistant	4
Blade Cut Resistant	X
Tear Strength Resistance	4
Puncture Resistance	3
Cut Resistance Method	D
Impact Protection	-

Users Instruction:

1.) APROVED STANDARD:

The gloves meet the European regulation EU 2016/425 on personal protection against mechanical risks. They meet all relevant technical ENstandards EN388:2016.

2.) USER PRECAUTION:

- Check before use if the gloves do not show any defects. It is not recommended to use the gloves in the proximity of machines in operation. Do not use gloves that are dirty because of the risks of dermatitis.
- Some gloves can contain products (such as rubber, latex) that may cause allergic reactions. By preference keep the gloves in a dry place inside the original packaging. Keep the gloves away from any heat source.
- The gloves don't offer protection against chemical fluids.

3.) LIFESPAN

The gloves can be expected to remain in service for 2 years or more, when it is in well stored condition.

4.) CLEANING

The gloves can be cleaned with a normal detergent at a maximum temperature of 40°C. After cleaning, the gloves generally keep their characteristics. Nevertheless, we cannot be held liable in case any safety properties are reduced.

5.) STORAGE

Store the gloves in a cool, dry and clean place out of direct sunlight. Avoid area where heat, moisture, light, oil, or their vapours or other degrading elements may be present.

